



William Hackett

www.williamhackett.co.uk

Mounted Harrows

All frame wings have gusset plates welded to the corners to add strength and rigidity to the frame. To make the frames universal, chains are welded along the front and rear bars so any type of harrow selection can be accommodated. Mounted harrows are available in widths of 6'-0" through to 16'-0" wide with a depth of 7'-6", frames of 10'-0" and over have folding wings for ease of transportation.

The smaller frames are rigid and delivered flat packed on pallets. All frames are supplied for self assembly. Mounting brackets are fitted to frames from 12'-0" and over to make retro fitting of the hydraulic folding kit easier.

Folding is a simple one man operation taking only seconds. Hydraulic folding is an optional extra on all folding frames.

Our mounted harrows are designed to pull the harrows at the correct angle so that the ground is completely covered.



Mounted Frame Attachment

All Mounted Frames are supplied in flatpack form for self assembly and ease of transportation. Frames 6'-0" to 8'-0" wide are of bolt together construction and those 10'-0" wide and over consist of a fabricated and welded centre frame and folding wing sections. Comprehensive assembly instructions are supplied with all mounted harrows.

All Universal Frames are constructed from 60mm x 60mm R.H.S. for additional strength and rigidity.

All frame wings have gusset plates welded to the corners (Pic. A) to add strength and rigidity to the frame. Chain links are welded along the front and rear bars (Pic. B) to accommodate our complete range of harrow sections.



Mounted Harrows are available in widths of 6'-0" through to 16'-0" wide and a depth of 7'-6", frames of 10'-0" and over have manual folding wings for ease of transportation along roads and through gateways.

Folding is a simple one person operation and a hydraulic folding kit (Pic. C) is available as an option on all folding frames. Mounting brackets are fitted, as standard, to frames from 12'-0" and over to make retro fitting of a folding kit easier.

Mounted Harrows Specifications

Type	Depth	Tine size	Working Widths and Weight (Kg) Complete						
			10'-0"	12'-0"	14'-0"	16'-0"			
4'-0"	6'-0"	8'-0"							
Heavy Grass	7'-6"	1/2" dia. x 2 1/2"	-	160	205	290	315	345	375
Chain and Spike	7'-6"	1/2" dia. x 3 1/2"	-	195	240	320	350	390	422
Paddock Grass	5'-0"	1/2" dia. x 2 1/2"	115	125	145	-	175	-	-
Paddock Flexible	5'-0"	1/2" dia. x 2 1/2"	125	155	170	-	215	-	-



William Hackett

William Hackett Lifting Products Ltd Oak Drive, Lionheart Enterprise Park, Alnwick, Northumberland NE66 2EU
Email: liftingsales@williamhackett.co.uk Tel: +44 (0)1665 604200 Fax: +44 (0)1665 604204

Web: www.williamhackett.co.uk



Better connected with William Hackett