




Yoke Grade 10 Clevis Shackle

All Grade 10 lifting components sold by William Hackett Lifting Products comply fully with the relevant section of EN1677, ASTM A952/A and DIN PAS 1061. The grade 10 components are forged from alloy steel, they are crack detected following heat treatment and finally proof tested to 2.5 times working load. The full compliance of these components means that they can be used in chain slings certified to EN 818-4, for use in a temperature range of -40°C up to 200°C without reduction in working load limit.



METRIC SPECIFICATIONS

Part Code	Chain Size mm	A mm	C mm	G mm	K mm	L mm	M mm	W mm	WLL tonnes	Box Quantity	Mass Kg
X-066-07	7,8	9	79	34	59	35	16	33	2.5	35	0.4
X-066-10	10	11	93	40	78	48	20	37	4.0	20	0.8
X-066-13	13	14	118	44	98	64	22	49	6.7	18	1.4
X-066-16	16	18	141	54	112	69	28	60	10.0	10	2.5

IMPERIAL SPECIFICATIONS

Part Code	Chain Size inch	A inch	C inch	G inch	K inch	L inch	M inch	W inch	WLL lbs	Box Quantity	Mass lbs
X-066-07	5/16	0.35	3.11	1.34	2.32	1.38	0.63	1.30	5500	35	0.88
X-066-10	3/8	0.43	3.66	1.57	3.07	1.89	0.78	1.45	8800	20	1.76
X-066-13	1/2	0.55	4.64	1.73	3.86	2.52	0.86	1.93	14700	18	3.08
X-066-16	5/8	0.70	5.55	2.13	4.40	2.72	1.10	2.36	22000	10	5.51

