


## Yoke Grade 8 Clevis Grab Hook BS EN1677-1+2

All Grade 8 lifting components sold by William Hackett Lifting Products comply fully with the relevant section of EN1677, they are forged from alloy steel, they are crack detected following heat treatment and finally proof tested to 2.5 times working load. The full compliance of these components means that they can be used in chain slings certified to EN 818-4, for use in a temperature range of -40°C up to 200°C without reduction in working load limit.



### METRIC SPECIFICATIONS

Part Code	Chain Size mm	A mm	F mm	H mm	K mm	L mm	P mm	WLL tonnes	Box Quantity	Mass Kg
8-042-07	7, 8	9	30	25	55	93	10	2.00	70	0.30
8-042-10	10	12	41	35	77	128	13	3.15	30	0.80
8-042-13	13	15	53	42	97	152	16	5.30	15	1.60
8-042-16	16	17	58	45	102	180	20	8.00	8	2.80
8-042-20	20	23	98	54	124	217	23	12.50	4	4.80

### IMPERIAL SPECIFICATIONS

Part Code	Chain Size inch	A inch	F inch	H inch	K inch	L inch	P inch	WLL lbs	Box Quantity	Mass lbs
8-042-07	1/4 - 5/16	0.35	1.18	0.98	2.17	3.66	0.39	4500	70	0.70
8-042-10	3/8	0.47	1.61	1.38	3.03	5.04	0.51	7100	30	1.80
8-042-13	1/2	0.59	2.09	1.65	3.82	5.98	0.63	12000	15	3.50
8-042-16	5/8	0.67	2.22	1.77	4.47	7.66	0.79	18100	8	6.20
8-042-20	3/4	0.91	3.86	2.13	4.88	8.54	0.91	28300	4	11.0