


Yoke Grade 8 Reeveable Egg Link BS EN 1677-1+2

All Grade 8 lifting components sold by William Hackett Lifting Products comply fully with the relevant section of EN1677, they are forged from alloy steel, they are crack detected following heat treatment and finally proof tested to 2.5 times working load. The full compliance of these components means that they can be used in chain slings certified to EN 818-4, for use in a temperature range of -40°C up to 200°C without reduction in working load limit.



METRIC SPECIFICATIONS

Part Code	Chain Size mm	A mm	G mm	H mm	K mm	L mm	T mm	WLL tonnes	Box Qty	Mass Kg
8-059-07	7,8	9	65	15	99	80	15	2.0	40	0.4
8-059-10	10	11	80	18	125	100	19	3.15	20	0.8
8-059-13	13	14	108	22	168	136	25	5.3	10	1.5
8-059-16	16	18	124	26	198	158	27	8.0	8	2.4

IMPERIAL SPECIFICATIONS

Part Code	Chain Size inch	A inch	G inch	H inch	K inch	L inch	T inch	WLL lbs	Box Qty	Mass lbs
8-059-07	1/4 - 5/16	0.35	2.56	0.59	3.90	3.15	0.59	4500	40	0.9
8-059-10	3/8	0.43	3.15	0.71	4.92	3.94	0.75	7100	20	1.8
8-059-13	1/2	0.55	4.25	0.87	6.62	5.35	0.98	12000	10	3.3
8-059-16	5/8	0.71	4.88	1.02	7.80	6.50	1.07	18100	8	5.3