



## 3-dobbel og 4-dobbel kjettingslynge EN 818-4

| Kjettingsstørrelse<br>mm | Rett løft<br>0°-45° | Rett løft<br>45°-60° | Koblingsfeste<br>0°-45° | Koblingsfeste<br>45°-60° | Dobbel kurv<br>0°-45° | Dobbel kurv<br>45°-60° |
|--------------------------|---------------------|----------------------|-------------------------|--------------------------|-----------------------|------------------------|
| 7mm                      | 3.1                 | 2.2                  | 2.5                     | 1.7                      | 3.15                  | 2.2                    |
| 8mm                      | 4.2                 | 3.0                  | 3.3                     | 2.4                      | 4.2                   | 3.0                    |
| 10mm                     | 6.7                 | 4.75                 | 5.3                     | 3.8                      | 6.7                   | 4.75                   |
| 13mm                     | 11.2                | 8.0                  | 8.9                     | 6.4                      | 11.2                  | 8.0                    |
| 16mm                     | 17.0                | 11.8                 | 13.6                    | 9.4                      | 17.0                  | 11.8                   |
| 20mm                     | 26.5                | 19.0                 | 21.2                    | 15.2                     | 26.5                  | 19.0                   |
| 22mm                     | 31.5                | 22.4                 | 25.2                    | 17.9                     | 31.5                  | 22.4                   |
| 26mm                     | 45.0                | 31.5                 | 36.0                    | 25.2                     | 45.0                  | 31.5                   |
| 32mm                     | 67.0                | 47.5                 | 53.6                    | 38.0                     | 67.0                  | 47.5                   |

Alle laster vises i tonn

